

Chapter 16-125 WAC
FARM MILK STORAGE TANKS AND BULK MILK TANKER—REQUIREMENTS

Last Update: 8/25/99

WAC

16-125-010 Definitions.
16-125-020 Construction.
16-125-030 Installation.
16-125-035 Farm tank pickup and washing requirements.
16-125-120 Bulk milk tanker requirements.
16-125-200 Recording thermometers—Installation.
16-125-210 Recording thermometer—Operation.

DISPOSITION OF SECTIONS FORMERLY CODIFIED IN THIS CHAPTER

16-125-001 Promulgation. [Order 1283, § 16-125-001, filed 1/29/73.] Repealed by WSR 84-18-055 (Order 1840), filed 9/5/84. Statutory Authority: Chapter 15.36 RCW.
16-125-040 Tolerances. [Order 1283, § 16-125-040, filed 1/29/73.] Repealed by WSR 99-18-032, filed 8/25/99, effective 9/25/99. Statutory Authority: RCW 15.36.020.
16-125-050 Authorized calibrators. [Order 1283, § 16-125-050, filed 1/29/73.] Repealed by WSR 99-18-032, filed 8/25/99, effective 9/25/99. Statutory Authority: RCW 15.36.020.
16-125-060 Calibration charts. [Order 1283, § 16-125-060, filed 1/29/73.] Repealed by WSR 99-18-032, filed 8/25/99, effective 9/25/99. Statutory Authority: RCW 15.36.020.
16-125-070 Calibration required. [Order 1283, § 16-125-070, filed 1/29/73.] Repealed by WSR 99-18-032, filed 8/25/99, effective 9/25/99. Statutory Authority: RCW 15.36.020.
16-125-080 Calibration (gaging) procedure. [Order 1283, § 16-125-080, filed 1/29/73.] Repealed by WSR 99-18-032, filed 8/25/99, effective 9/25/99. Statutory Authority: RCW 15.36.020.
16-125-090 Checking (testing) procedure. [Order 1283, § 16-125-090, filed 1/29/73.] Repealed by WSR 99-18-032, filed 8/25/99, effective 9/25/99. Statutory Authority: RCW 15.36.020.
16-125-100 Sealing legs. [Order 1283, § 16-125-100, filed 1/29/73.] Repealed by WSR 99-18-032, filed 8/25/99, effective 9/25/99. Statutory Authority: RCW 15.36.020.
16-125-110 Effective date. [Order 1283, § 16-125-110, filed 1/29/73.] Repealed by WSR 84-18-055 (Order 1840), filed 9/5/84. Statutory Authority: Chapter 15.36 RCW.

WAC 16-125-010 Definitions. (1) "Director" means the director of the department of agriculture, or his/her duly authorized representative.

(2) "Bulk milk hauler" means the licensed dairy technician who has primary responsibility for the measuring, weighing, or grading of milk and the collection of samples at the farm.

(3) "Bulk milk hauling" means the transportation of milk or milk products from the producer to a milk processing plant or between milk processing plants, by vehicles belonging to an individual or corporation operating under a bulk milk hauler's license.

(4) "3A standards" means current sanitary standards for dairy equipment and accepted practices as published in the *Dairy Food and Environmental Sanitation* magazine of the International Association of Milk, Food and Environmental Sanitarians (IAMFES).

[Statutory Authority: RCW 15.36.020. WSR 99-18-032, § 16-125-010, filed 8/25/99, effective 9/25/99. Statutory Authority: Chapter 15.36 RCW. WSR 84-18-055 (Order 1840), § 16-125-010, filed 9/5/84; Order 1283, § 16-125-010, filed 1/29/73.]

WAC 16-125-020 Construction. All new farm tanks must conform with the 3-A sanitary standards for farm milk cooling and holding tanks. Whenever a ladder or platform is needed for sampling, measuring or other purposes, it must be permanently attached to the tank or a wall. All calibrated rods must be identified with the serial number of the tank. Sight glass tubes must be of one-piece construction and permanently attached to the farm tank. All sight glass tubes must be cleaned with a clean-in-place (C.I.P.) system.

[Statutory Authority: RCW 15.36.020. WSR 99-18-032, § 16-125-020, filed 8/25/99, effective 9/25/99; Order 1283, § 16-125-020, filed 1/29/73.]

WAC 16-125-030 Installation. Before any person installs a new tank or relocates a used tank, he or she must file drawings and detailed information about where and how the milk storage tank is to be installed with the director. There must be a minimum of two feet clearance between the sides of the tank and the walls of the milkhouse or other permanent equipment and a minimum of three feet on the working side of the tank and at the outlet valve. Adequate additional space necessary for normal milkhouse operations must be provided. There must be at least 30 inches clearance between the top of the pouring tank lip and the ceiling. Adequate space must be provided above the tank to accommodate the measuring rod.

Provisions of the National Bureau of Standards' Handbook 44 Code on Farm Milk Tanks as adopted under chapter 19.94 RCW applicable to installation and use shall be applicable.

[Statutory Authority: RCW 15.36.020. WSR 99-18-032, § 16-125-030, filed 8/25/99, effective 9/25/99; Order 1283, § 16-125-030, filed 1/29/73.]

WAC 16-125-035 Farm tank pickup and washing requirements. (1) All milk must be picked up at least every forty-eight hours from farm tanks.

(2) All farm tanks must be emptied, washed and sanitized at least once every forty-eight hours.

[Statutory Authority: RCW 15.36.020. WSR 99-18-032, § 16-125-035, filed 8/25/99, effective 9/25/99.]

WAC 16-125-120 Bulk milk tanker requirements. All bulk milk tankers operating in the state of Washington must comply with the provisions of 3A standard 05-14. Additional requirements are:

(1) Trucks and trailers with remote pumps, mounted on tractor or front trailer, and a system of external hoses and/or piping may be used: Provided, That

(a) External flexible hoses meet the following requirements:

(i) Hoses are the thick walled rubber type and meet 3A standards 18-01, 62-01 and 63-01 except for pump box hoses.

(ii) Hoses are capped with a sanitary cap when not in use.

(b) Piping along the length of the trailer is of the fixed type and meets the following requirements:

(i) The pipe is stainless steel and meets the requirements of 3A standards 63-02 and 33-01. Other materials may be used if they are approved by the Milk Safety Branch of the Food and Drug Administration.

(ii) The sanitary piping is enclosed in an insulated holder and both the sanitary piping and the holder are capped with a dust tight cap when disconnected.

(c) Sanitary air that meets the requirements of 3A standard 64-04 may be used to remove residual milk from the external piping system.

(d) Any milk in the external piping system that exceeds forty-five degrees Fahrenheit is discarded.

(e) Adequate facilities must be provided at all receiving stations for the proper cleaning and sanitizing of tankers including the external lines and valves.

(2) All external valves on a tanker must be provided with a means of protection against dust, dirt, and road debris.

(a) Outlet valves must be protected by dust tight covers that will comply with 3A standard 05-14.

(b) Inlet valves and valves with attached hoses must be protected by a relatively dust tight cover. This cover may be:

(i) Stainless steel with an opening for the connection of hoses that is sealed with a flexible material that will prevent the entrance of dust, dirt, or road debris.

(ii) A flexible mounting made of rubber or other approved material that is close fitting, smooth, impervious, and easily removable for cleaning.

(iii) Any other cover for which plans have been submitted to and approved by the director.

(c) All valves not connected to hoses must have a sanitary cap and an approved dust cover on them.

(3) Markings on each truck or trailer must be sufficient to identify the owner of the truck or trailer.

(4) Cleaning and bactericidal treatment of all product contact surfaces including valves, hoses, covers, connections, appurtenances, pumps, and pump compartment of each tanker, when used, must be accomplished at least once every twenty-four hours after first use. If the tanker is not used for hauling milk for seventy-two hours after cleaning and sanitizing it must be sanitized again before it may be used for hauling milk. After sanitization each tanker must be tagged to show the date washed, place washed, and initials or signature of the person who washed the tanker. This wash tag must not be removed until the tanker is rewashed. It shall be the responsibility of the bulk milk hauler to ensure that the wash tag is present and that the tank is in fact clean prior to commencing his route.

(5) Plans and drawings relating to tankers submitted to the director will be treated with confidentiality except as required under Public Disclosure Act, chapter 42.17 RCW.

(6) Bulk milk tankers must meet the requirements under chapter 69.04 RCW and the rules adopted thereunder for transportation of food.

[Statutory Authority: RCW 15.36.020. WSR 99-18-032, § 16-125-120, filed 8/25/99, effective 9/25/99. Statutory Authority: Chapter 15.36 RCW. WSR 84-18-055 (Order 1840), § 16-125-120, filed 9/5/84.]

WAC 16-125-200 Recording thermometers—Installation. (1) All new farm bulk tank installations must include a recording thermometer and an automatic interval timer. Installation of a used milk tank will be regarded as a new installation.

(2) The installation and operation of recording thermometers and interval timers shall be the responsibility of the holder of the Grade A producer permit.

(3) Recording devices must not be attached to a farm tank. Recording devices may be suspended on metal brackets from the ceiling, firmly attached to the inside wall of the milk room, or at any other

location acceptable to the department. The recording device must be mounted no more than six feet from the floor or be otherwise accessible from the floor without the necessity of climbing.

(4) The sensor bulb or device must be located so as to record the temperature of the milk in the tank before the milk reaches twenty percent of the tank volume. A capillary system containing toxic gas or liquids must not be used in a bare bulb sensor device.

(5) The recorder and chart must be capable at a minimum of recording from thirty-two degrees to one hundred eighty degrees F, or above, and must be accurate within plus or minus two degrees F.

(6) The case of the recording device must be moisture-proof under operating conditions in the milk house or milk room.

(7) The recording chart must make at a minimum one revolution every seven days. A strip chart must not be used.

(8) The recording clock must be electrically operated. The recorder pen must be set to the actual time.

(9) If at any time, the recording device becomes inoperable or out of tolerance, the inspection service and the pooling agent or hauler must be notified immediately by the producer. Repair or replacement of the device must be made as soon as possible.

(10) The producer must maintain an adequate supply of recording charts. The charts must fit the specific instrument installed.

(11) To prevent stratification of the milk in the tank the interval timer must be set so the milk will be agitated for at least five minutes every hour.

[Statutory Authority: RCW 15.36.020. WSR 99-18-032, § 16-125-200, filed 8/25/99, effective 9/25/99. Statutory Authority: Chapter 15.36 RCW. WSR 86-17-014 (Order 1902), § 16-125-200, filed 8/8/86.]

WAC 16-125-210 Recording thermometer—Operation. (1) Milk and milk products for consumption in the raw state or for pasteurization must be cooled to forty degrees F or lower within two hours after completion of milking and maintained at that temperature until picked up: Provided, That the blend temperature after the first and subsequent milkings may not exceed fifty degrees F.

(2) In making a milk pick-up, the licensed grader and sampler must:

(a) Remove the chart from the recorder before the chart has lapsed;

(b) Mark the date and time of pick-up;

(c) Sign the chart;

(d) Date and install a new chart, if necessary;

(e) File the completed charts under protected conditions, provided for by the producer, unless they are taken to the purchaser's premises for his review.

(f) If the charts are taken from the dairy farm, they must be returned within ten days from the date they were taken: Provided, That subject to the approval of its members and the department, a pooling agent, processing plant, receiving plant or regular place of business may file the recording thermometer charts at its place of business.

(g) The official milk temperature must be taken with an accurate, properly calibrated thermometer.

(3) The temperature recording charts may be used for more than one pick-up: Provided, That all the pick-ups occur within the maximum

time interval of the chart. When the chart is used for more than one pick-up, the licensed grader and sampler must identify each lot of milk with the date, time of pick-up and his/her signature.

(4) Before removing milk from a farm bulk tank, the licensed grader and sampler must check the recording chart. If the licensed grader and sampler finds milk temperature variations extending beyond the legal limits, he/she must immediately notify the producer, or in the absence of the producer, an employee, and the producer's marketing agent. The licensed grader and sampler must sign the chart noting the date, time, stick reading and indicate that a temperature infraction has occurred. The producer's marketing agent must notify the department of agriculture of temperature standard violations detected through the official milk quality testing program. Temperature standard violations reported to the department will become part of the producer's official record.

(5) Except as otherwise provided in subsection (2) of this section, recorder charts must be held at the dairy farm for ninety days and be made available to the director.

[Statutory Authority: RCW 15.36.020. WSR 99-18-032, § 16-125-210, filed 8/25/99, effective 9/25/99. Statutory Authority: Chapter 15.36 RCW. WSR 86-17-014 (Order 1902), § 16-125-210, filed 8/8/86.]