

WAC 173-182-390 Dungeness planning standard. Those covered vessel and facility plan holders that transit or operate within a five nautical mile radius of a point at Lat. 48°10'56"N Long. 123°06'38"W (WGS 1984) must meet the following standards.

Time (hours)	Boom/Assessment	Minimum Oil Recovery Rate % of WCS volume per 24 hours	Minimum Storage Volume
2	A safety assessment of the spill by work boat with trained crew and appropriate air monitoring, with 1,000 feet of boom could have arrived		
3	Additional 2,000 feet of boom, or 4 times the length of the largest vessel whichever is less, to be used for containment, protection or recovery could have arrived on scene		
6	Additional 7,000 feet of boom with at least 3,000 feet of open water boom for containment, protection or recovery could have arrived	Capacity to recover the lesser of 3% of worst case spill volume or 12,500 barrels within 24-hour period could have arrived. At least 50% must be capable of working in open water environments	1 times the EDRC
12	Additional 20,000 feet of boom appropriate for all potential areas of impact for containment, protection or recovery could have arrived	Capacity to recover the lesser of 10% of worst case spill volume or 36,000 barrels within 24-hour period could have arrived. At least 50% must be capable of working in open water environments	1.5 times the EDRC
24	Additional 20,000 feet combination of appropriate types of boom for containment, protection or recovery could have arrived	Capacity to recover the lesser of 14% of worst case spill volume or 48,000 barrels within 24-hour period could have arrived	2 times the EDRC
48	More boom as necessary for containment, recovery or protection	Capacity to recover the lesser of 25% of worst case spill volume or 60,000 barrels within 24-hour period could have arrived	More as necessary to not slow the response

[Statutory Authority: Chapters 88.46, 90.56, and 90.48 RCW. WSR 06-20-035 (Order 00-03), § 173-182-390, filed 9/25/06, effective 10/26/06.]